

Diamond Coil

Customer

T: 44 (0) 114 248 4391
E: coils@preformedwindings.com

Contact

Telephone

www.preformedwindings.com

Date

Motor manufacturer

Frequency

HP / KW / KVA

Serial no.

Frame no.

Revs per minute

Insulation class

Hard coil

Soft coil

Other

Machine voltage

Machine amps

Unit of measurement (please tick) mm inches

1	Core inside diameter	
2	Core length	
3	Finger plate width	
4	Number of slots	
5	Number of coils	
6	Total slot depth	
7	Coil space under wedges	
8	Slot width	
9	Slot skew left distance	
10	Slot skew right distance	
11	Turns per coil	
12	Conductor width	Thickness
13	No. of conductors in parallel	
14	Coil pitch	1 -
15	Weight of insulated coil	
16	Connection end coil projection	
17	Back end coil projection	
18	Overall coil length	
19	Coil slot length top leg	
20	Coil slot length bottom leg	
21	Bracing ring:	
	- Distance from core connection end	
22	- Distance from core back end	
23	- Internal diameter connection end	
24	- Internal diameter back	
25	- Fixed or floating	
26	Lead position	
27	Lead position	
28	Wound top left	
29	Wound top right	
30	Core to top of coil connection end	
31	Core to bottom of coil connection end	
32	Core to top of coil back end	
33	Core to bottom of coil back end	
34	Please tick	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> Other <input type="checkbox"/>

